

इंटरनेट

मानक

Disclosure to Promote the Right To Information

Whereas the Parliament of India has set out to provide a practical regime of right to information for citizens to secure access to information under the control of public authorities, in order to promote transparency and accountability in the working of every public authority, and whereas the attached publication of the Bureau of Indian Standards is of particular interest to the public, particularly disadvantaged communities and those engaged in the pursuit of education and knowledge, the attached public safety standard is made available to promote the timely dissemination of this information in an accurate manner to the public.

“जानने का अधिकार, जीने का अधिकार”

Mazdoor Kisan Shakti Sangathan

“The Right to Information, The Right to Live”

“पुराने को छोड़ नये के तरफ”

Jawaharlal Nehru

“Step Out From the Old to the New”

IS 5000-OD41 (1986): Dimensions of Semiconductor Devices,
Device Outline OD41 [LITD 5: Semiconductor and Other
Electronic Components and Devices]



“ज्ञान से एक नये भारत का निर्माण”

Satyanarayan Gangaram Pitroda

“Invent a New India Using Knowledge”



“ज्ञान एक ऐसा खजाना है जो कभी चुराया नहीं जा सकता है”

Bhartrhari—Nitiśatakam

“Knowledge is such a treasure which cannot be stolen”

BLANK PAGE







Indian Standard

DIMENSIONS OF SEMICONDUCTOR DEVICES DEVICE OUTLINE OD 41

1. Dimensions— This drawing has been prepared in accordance with IS : 5001 (Part 1)-1969 'Guide for preparation of drawings of semiconductor devices and integrated circuits : Part 1 Semiconductor devices'.



Reference	Millimetres			Notes
	Min	Nom	Max	
ϕD	—	—	48	—
ϕD_1	—	—	—	1, 2
F	10	—	—	—
J	—	—	110	1, 3
ϕM	—	—	—	4
M_1	—	—	26.5	5, 6
M_2	—	—	10.0	5, 6
N_1	—	—	4.0	—
O_1	225	—	—	7
O_2	—	—	275	7
ϕT_1	10.0	—	10.5	—
ϕT_2	3.0	—	5.0	—
Z_1	10.0	—	—	8
Z_2	3.0	—	—	8



Adopted 4 April 1986

© March 1987, ISI

Gr 1

Reference	Type A			Type B		
	Min	Nom	Max	Min	Nom	Max
<i>E</i>	—	41	—	—	41	—
<i>N</i>	19	—	26	12	—	14
<i>W</i>	M24×1.5			M24×1.5		

Note 1 — The device, with exception of the hexagon, thread and flexible lead lies within the cylinder of diameter D_1 and length J .

Note 2 — Diameter D_1 must not be greater than the actual across flats dimension of the hexagon used.

Note 3 — Dimension J is the seated height with the leads bent at right angles.

Note 4 — Diameter M refers to zone N_1 . The maximum value should not exceed the outside diameter of the thread.

Note 5 — The contour and orientation of the terminal slug of lug are undefined.

Note 6 — The large terminal lug is No. 1, the small terminal lugs are No. 2 and No. 3.

Note 7 — The actual value of dimension O_2 is greater than that of O_1 .

Note 8 — Minimum flat.

Note 9 — The terminal lugs No. 3 may not exist in Type B.

2. Rules for Coding — See 8.1 of IS : 5001 (Part 1)-1969.

3. Equivalent Designations

Country or Organization	Code	
	Type A	Type B
IEC	A 29 MA	A 29 MB
Japan	SC-20 Δ	—
Germany	207 B 4	207 A 4 Δ
USSR	—	K 712 P 1 Δ